



PISTON DE 3 SECCIONES SIN TUERCA 14 MTS FEE3-149-2743



PRAT[®]
REFACCIONARIA

   
@PRAT.REFACCIONARIA



B978

El Pistón de 3 secciones sin tuerca 14 mts PR FEE3-149-2743 es un componente hidráulico de alto rendimiento diseñado para aplicaciones de elevación y extensión en equipos pesados. Este pistón telescópico de tres etapas proporciona un despliegue de hasta 14 metros, ideal para sistemas de volteo.

Technical drawing of a mechanical component, showing two views: a front view (top) and a side view (bottom).

Front View (Top):

- Overall length: 1305 ± 5
- Flange diameter: $\phi 52.5^{+0.2}_0$
- Flange thickness: $R61$
- Mounting bracket width: 90
- Mounting bracket hole diameter: $\phi 17$
- Mounting bracket hole position: $NP T1$
- Mounting bracket hole diameter: $\phi 17$
- Mounting bracket hole position: $NP T1$
- Mounting bracket hole diameter: $\phi 17$
- Mounting bracket hole position: $NP T1$

Side View (Bottom):

- Overall width: 219 ± 0.5
- Mounting bracket width: 219 ± 0.5
- Mounting bracket hole diameter: $\phi 17.1$
- Mounting bracket hole position: $NP T1$
- Mounting bracket hole diameter: $\phi 17.1$
- Mounting bracket hole position: $NP T1$
- Mounting bracket hole diameter: $\phi 17.1$
- Mounting bracket hole position: $NP T1$

PRAT
REFACCIONARIA